

# INTERMERCATO Rotating Five Finger Grapple



## KEY FEATURES

- Made of Hardox
- Extra reinforced body for rigid mounting
- Hardox guide bars from TG16PRO
- Holds load steady at any angle (with optional brake)
- Steel gears & flange for increased durability
- High Pressure Construction
- High torque
- Optimized positioning performance
- Endless 360° rotation
- Optional solenoid if only one set of auxiliaries available
- Custom builds

MODEL SPECIFICATIONS	RIGID 	WEIGHT 	GRIP AREA 	PRESSURE 	FLOW 	CLAMPING 	OPENING WIDTH 	CLOSING WIDTH 	WORM DRIVE ROTATOR 
	ton	Kg	m <sup>2</sup>	Bar	l/min	kN			
TG12SR5WD7	1.5-2	115	0.12	200	15-30	8	810	38	WD7
GRX15-5 WD7	2-3.5	185	0.14	200	20	7.2	940	63	WD7
GRX20-5 WD9	3.5-5.5	285	0.19	200	30	11.3	1234	78	WD9
GRX25-5 WD9	5-7.5	375	0.24	250	40	14.9	1385	85	WD9
TG28SR5WD14	7-12	500	0.30	250	60	15	1500	95	WD14
TG35SR5WD14/2	10-12	540	0.38	250	60	18	1890	65	WD14/2
TG42SR5WD17/2	12-16	650	0.50	250	70	25	1895	100	WD17/2
TG55SR5WD21/2	16-21	1235	0.65	250	90	25	2425	150	WD21/2

## HEAVY DUTY OPTION

GX28WD17/2	12-18	800	0.28	350	60	20	1486	130	WD17/2
GX36WD21/2	18-24	1250	0.36	350	60	20	1800	135	WD21/2
GX36WD25/2	24-30	1350	0.36	350	60	20	1800	135	WD25/2
GX55WD25/2	24-32	2500	0.50	350	70	50	2295	145	WD25/2

# INTERMERCATO

High performance lift and load attachments for Forestry, Transport, Construction and Recycling.

