

We accept no substitute

KEY FEATURES




Aussie-Made Head Bracket

- Low-profile, bolt-on design
- Custom-built to suit your excavator

European-Engineered Grapple

- Built for fast, efficient demolition and on-site sorting
- Save on landfill costs by sorting mixed materials with ease
- Fully constructed from **HARDOX** for unmatched strength and wear resistance
- **Reversible 500HB HARDOX cutting edges** for extended life
- From TG20DG up: **self-lubricating graphite bushes** for lower maintenance
- **High-pressure hydraulic cylinder** for powerful, reliable clamping
- **Optional rotator** for 360° material handling flexibility

Tough enough to tear it down. Smart enough to clean it up.
Contact us today for pricing and availability.

MODEL SPECIFICATIONS	RIGID MOUNTING 	WEIGHT INCL. HEADBRACKET 	WEIGHT 	GRIP AREA 	PRESSURE 	FLOW 	CLAMPING 	OPENING WIDTH 	CUTTING EDGE WIDTH 
TG15 DG	3.5-8.0	220	190	0.14	250	+30	18	1154	390
TG18 DG	8.0-12	420	360	0.18	250	+30	19	1430	530
TG20 DG	10-16	750	650	0.2	300	60	33	1560	530
TG25 DGL	14-24	975	850	0.35	300	90	57	1940	800
TG25 DG	14-26	1100	975	0.35	300	90	57	1940	800
TG30 DG	22-32	1600	1465	0.5	300	90	69	2350	1000