



We accept no substitute

### KEY FEATURES

#### Aussie-Made Head Bracket

- Low-profile, bolt-on design
- Custom-built to suit your excavator

#### European-Engineered Grapple

- Built for fast, efficient demolition and on-site sorting
- Save on landfill costs by sorting mixed materials with ease
- Fully constructed from **HARDOX** for unmatched strength and wear resistance
- **Reversible 500HB HARDOX cutting edges** for extended life
- From TG20DG up: **self-lubricating graphite bushes** for lower maintenance
- **High-pressure hydraulic cylinder** for powerful, reliable clamping
- **Optional rotator** for 360° material handling flexibility

Tough enough to tear it down. Smart enough to clean it up.  
Contact us today for pricing and availability.

MODEL SPECIFICATIONS	RIGID MOUNTING	WEIGHT INCL. HEADBRACKET	WEIGHT	OPENING WIDTH	CUTTING EDGE WIDTH	CLAMPING	GRIP AREA	PRESSURE	FLOW
									
TG15DG	3.5-8.0	220	190	1154	390	18	0.14	250	+30
TG18DG	8.0-12	390	340	1430	530	19	0.18	250	+30
TG20DG	10-16	565	495	1560	530	33	0.2	300	60
TG25DGL	14-24	900	810	1940	800	57	0.35	300	90
TG25DG	14-26	1000	900	1940	800	57	0.35	300	90
TG30DG	22-32	1450	1325	2350	1000	69	0.5	300	90