


HIGH
TORQUE
WORM DRIVE



KEY FEATURES

Head Bracket - Aussie Made

- Bolt-on, flat for tilt hitch or angled for upright tree/pole handling










Grapple - Made in Europe

- Hardox for strength and durability
- Exclusive long finger design for better penetration and material control
- Optimized geometry for better bunching
- Hydraulic – operates independently from the dipper for full range of movement

Worm Drive Rotator

- 360° rotation with specially designed low gearing for a long life
- NSL – non self-locking design protects worm drive
- Holds load at any angle (optional brake)
- Feed chippers without moving the machine
- Grip trees upright, then lower safely

Optional solenoid if only one set of auxiliaries available

KOMATSU MODELS	MODEL SPECIFICATIONS	RIGID	WEIGHT	GRIP AREA	PRESSURE	FLOW	CLAMPING	OPENING WIDTH	CLOSING WIDTH	WORM DRIVE ROTATOR
		 ton	 Kg	 m ²	 Bar	 l/min	 kN			
PC18	GRX10-5 WD7	1.5-2	125	0.11	200	15-30	7.2	976	60	WD7
PC25MR & PC30MR	GRX15-5 WD7	2.0-3.5	185	0.14	200	20	7.2	940	63	WD7
PC35MR & PC45MR	GRX20-5 WD9	3.5-5.5	285	0.19	200	30	11.3	1234	78	WD9
PC55MR	GRX25-5 WD9	5.0-7.5	375	0.24	250	40	15	1385	85	WD9
PC78UU & PC88MR	GRX30-5 WD14/2	8.0-12	480	0.29	300	50	18.3	1587	105	WD14 /2
PC130 & PC138US	TG42SR5 WD17/2	12-16	650	0.50	250	70	25	1895	100	WD17/2
PC170	TG55SR5 WD21/2	16-21	1235	0.65	250	90	25	2425	150	WD21/2
HEAVY DUTY OPTION										
PC130, PC138US & PC170	GX28-50/5 WD17/2	12-18	800	0.28	350	60	20	1486	130	WD17/2
PC200, PC210 & HB215	GX36-50/5 WD21/2	18-24	1250	0.36	350	60	20	1800	135	WD21/2
PC220, PC228, PC240 & PC270	GX36-50/5 WD25/2	24-30	1350	0.36	350	60	20	1800	135	WD25/2
PC290 & PC300	GX55-50/5 WD25/2	24-32	2500	0.50	350	70	50	2295	145	WD25/2