




Bobcat[®] DEVELON

INTERMERCATO Rotating Five Finger Grapple - Worm Drive

HIGH
TORQUE
WORM DRIVE



KEY FEATURES

Head Bracket - Aussie Made

- Bolt-on, flat for tilt hitch or angled for upright tree/pole handling

Grapple - Made in Europe

- Hardox for strength and durability
- Exclusive long finger design for better penetration and material control
- Optimized geometry for better bunching
- Hydraulic – operates independently from the dipper for full range of movement

Worm Drive Rotator

- 360° rotation with specially designed low gearing for a long life
- NSL – non self-locking design protects worm drive
- Holds load at any angle (optional brake)
- Feed chippers without moving the machine
- Grip trees upright, then lower safely

Optional solenoid if only one set of auxiliaries available

BOBCAT MODELS	MODEL SPECIFICATIONS	RIGID	WEIGHT	GRIP AREA	PRESSURE	FLOW	CLAMPING	OPENING WIDTH	CLOSING WIDTH	WORM DRIVE ROTATOR
		ton	Kg	m ²	Bar	l/min	kN			
E10, E17 & E20	GRX10-5 WD7	1.5-2	125	0.11	200	15-30	7.2	976	60	WD7
E20, E30 & E35	GRX15-5 WD7	2.0-3.5	185	0.14	200	20	7.2	940	63	WD7
E35 & E50	GRX20-5 WD9	3.5-5.5	285	0.19	200	30	11.3	1234	78	WD9
E55	GRX25-5 WD9	5.0-7.5	375	0.24	250	40	15	1385	85	WD9
E88	TG28SR5 WD14	7.0-12	500	0.30	250	60	15	1500	95	WD14
E88	GRX30-5 WD14/2	8.0-12	480	0.29	300	50	18.3	1587	105	WD14 /2
DEVELON MODELS										
DX140	TG42SR5 WD17/2	12-16	650	0.50	250	70	25	1895	100	WD17/2
DX140 & DX190	GX28-50/5 WD17/2	12-18	800	0.28	350	60	20	1486	130	WD17/2
DX190 & DX225	GX36-50/5 WD21/2	18-24	1250	0.36	350	60	20	1800	135	WD21/2
DX240	GX36-50/5 WD25/2	24-30	1350	0.36	350	60	20	1800	135	WD25/2
DX240 & DX300	GX55-50/5 WD25/2	24-32	2500	0.50	350	70	50	2295	145	WD25/2

INTERMERCATO

High performance lift and load attachments for Forestry, Transport, Construction and Recycling.

