INTERMERCATO | Rotating Five Finger Grab

FAST ROTATION



KEY FEATURES

- *Rotator RMR - Austrian*
- *Rotator XR - Swedish*
- *Extra reinforced body for rigid mounting*
- *Hardox guide bars*
- *Fast & efficient rotation but not designed to hold load steady*
- *High torque*
- *Endless 360 rotation*
- *Optional solenoid if only one set of auxiliaries available*
- *Custom builds*

MODEL SPECIFICATIONS	RIGID ton	WEIGHT Kg	GRIP AREA m²	FLOW l/min	CLAMPING kN	OPENING WIDTH	CLOSING WIDTH	RMR ROTATOR
GRX10-5 RMR3	1.0-2.0	105	0.12	15-30	8.0	810	38	RMR3
GRX15-5 RMR3	2.0-3.5	140	0.14	20	7.2	940	63	RMR3
GRX20-5 RMR6	3.0-5.0	250	0.19	30	11.3	1234	78	RMR6
GRX25-5 RMR6	4.5-6.0	320	0.24	40	15	1385	85	RMR6
GRX25-5 RMR12	5.0-7.5	380	0.24	40	15	1385	85	RMR12
TG28SR5 RMR12	7.0-12	440	0.30	60	15	1500	95	RMR12
GRX30-5 RMR12	8-12	465	0.39	50	18.3	1587	105	RMR12
TG42SR5 XR350	12-16	680	0.50	70	25	1895	100	XR350
TG55SR5 XR350	16-21	1080	0.65	90	25	2425	150	XR350
HEAVY DUTY OPTION								
GX28 XR350	12-20	720	0.28	60	20	1486	130	XR350
GX36 XR600	20-30	1350	0.36	60	20	1800	135	XR600
GX55 XR600	24-32	2300	0.50	70	50	2295	145	XR600