



TG20-30



GRX15-25EG

KEY FEATURES

- Rotator RMR - Austrian
- Rotator XR - Swedish
- Fast rotator to work efficiently
- Double guide bars - TG Series
- Cylinder with double piston rod seals for high pressure
- HARDOX chassis - high tensile wear resistant steel (400 HB)
- **HARDOX - Reversible cutting edges in high tensile wear resistant steel (400 HB)**
- Pilot operated check valve optional



We accept no substitute



MODEL SPECIFICATIONS	RIGID MOUNTING 	TOTAL WEIGHT  Kg	GRIP AREA  m ²	PRESSURE  Bar	FLOW  l/min	CLAMPING  kN	OPENING WIDTH 	CUTTING EDGE WIDTH 	ROTATOR 	TORQUE  Nm
GRX10EGRMR3	1.0-2.0	110	0.8	200	15	7	950	345	RMR3	1300
GRX15EGRMR3	2.0-3.5	150	0.1	200	20	7	1150	365	RMR3	1300
GRX20EGRMR6	3.5-6.0	255	0.14	250	30	11	1300	395	RMR6	2800
GRX25EGRMR6	5.0-6.0	365	0.19	250	40	15	1500	440	RMR6	2800
GRX25EGRMR12	5.5-8.5	390	0.19	250	40	15	1500	440	RMR12	3800
TG28EGRMR12	8.0-12	490	0.2	250	50	19	1600	520	RMR12	3800
DEMOLITION SERIES - HEAVY DUTY										
TG20DGXR350	10-16	870	0.2	300	60	33	1560	530	XR350	4350
TG25DGLXR400	16-24	1175	0.35	300	90	57	1940	800	XR400	4100
TG25DGXR600	18-26	1400	0.35	300	90	57	1940	800	XR600	7000
TG30DGXR600	22-32	2000	0.5	300	90	69	2350	1000	XR600	7000